# CRS03 Angular Rate Sensor

# SILICON<sup>C</sup> SENSING

### CRS03-01T



#### CRS03-02T



A robust and affordable mass-produced gyroscope for automotive and commercial customers.

Angular rate sensors are used wherever rate of turn sensing is required without a fixed point of reference. The sensor will output a DC voltage proportional to the rate of turn and input voltage.

High performance motion sensing even under severe shock and vibration.

Whatever your application, the unique silicon ring technology, coupled with closed loop electronics, gives advanced and stable performance over time and temperature, overcoming the mount sensitivity problems experienced with simple beam or tuning fork based sensors.

#### Key features

- Two model types available
- Excellent performance over temperature
- Repeatable drift characteristic
- High shock and vibration operation
- High reliability
- Metalised housing
- FFF equivalent to CRS03-01S and CRS03-02S




© Silicon Sensing is an Atlantic Inertial Systems, Sumitomo Precision Products joint venture company


# CRS03 Angular Rate Sensor




### CRS03-01T

All dimensions in millimetres







CRS03-02T



Гуріcal Data	CRS03-01T	CRS03-02T	
Angular Rate Range	±100%s		Pin Connections
Output	Analogue voltage (ratiometric)		<b>1</b> +5V
Electrical Connections	Solder Pins	Connector	<b>2</b> 0V
Scale Factor			3 Rate Output
Nominal	20mV/°/s		
Variation over temperature range	< ±3%		
Non-linearity	$< \pm 0.5\%$ of full scale		
Bias			
Setting tolerance	< ±3°/s		
Variation over temperature range	< ±1°/S		
Ratiometric error	< ±1°/s		Ciliaan Canaing Customs Limited
Drift vs time	$< \pm 0.55^{\circ}$ /s in any 30s period (after start-up time)		Silicon Sensing Systems Limited Clittaford Road, Southway, Plymouth, Devon PL6 6DE United Kingdom
g sensitivity	$< \pm 0.1^{\circ}/\text{s/g}$ on any axis		
Bandwidth	10Hz (-3dB)		
Quiescent Noise	0.025% s rms		T +44 (0)1752 723330
Environment			F +44 (0)1752 723331 E sales@siliconsensing.com
Temperature	-40°C to +85°C		W siliconsensing.com
Linear acceleration	< 100g		Silicon Sensing Systems Japan Limited 1-10 Fuso-Cho, Amagasaki, Hyogo 6600891, Japan
Shock	200g (1ms, ½ sine)		
Vibration	2g rms (20Hz to 2kHz, random)		
Cross-axis sensitivity	< 5%		T +81 (0)6 6489 5868
Mass	< 18 gram		F +81 (0)6 6489 5919
Electrical			E sssj@spp.co.jp W siliconsensing.com
Supply voltage	+4.75V to +5.25V		
Supply current	< 35mA (steady state)		Specification subject to change without notice.
Noise and ripple	< 15mV rms (DC to 100Hz)		© Copyright 2016 Silicon Sensing Systems Limited
Start-up time	< 0.2s		All rights reserved. Printed in England 03/16
RoHS Compliant	Yes		CRS03T-00-0100-131 Rev 1 DCR No. 710011077

Silicon Sensing Systems Limited Registered in England & Wales No. 3635234 Clittaford Road, Southway, Plymouth, Devon PL6 6DE The device mark Silicon Sensing is a registered trade mark of Silicon Sensing Systems Community Trade Mark 003587664